Note: This datasheet may be out of date

Please download the latest datasheet of CFUKG455KH1X-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-US/products/productdetail?partno=CFUKG455KH1X-R0

CFUKG455KH1X-R0










Appearance & Shape







Applications

Other Usage	Communication Equipment
-------------	-------------------------



Packaging Information

Packaging	Specifications	Minimum Order Quantity
-R0	180mm Embossed Tape	450



Features

The CFUKG_X series is comprised of small, highperformance, thin (4.0mm) ffiters consisting of 4 ceramic elements. The ffiters exhibit an extremely ffat GDT characteristic combined with a narrow bandwidth. The ffiters are recommended for narrow band digital communication applications.

Features

- 1. The ffiters are mountable by automatic placers.
- 2. The ffiters can be refflow soldered and withstand washing.
- 3. They are slim, at only 4.0mm maximum thickness, and have a small mounting area (7.5x6.0mm) enabling flexible PCB design.
- 4. The bandwidth ranges from E to H.
- 5. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date.

Please download the latest datasheet of CFUKG455KH1X-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-US/products/productdetail?partno=CFUKG455KH1X-R0

CFUKG455KH1X-R0



Specifications

Operating Temperature Range	-20°C to 80°C		
Shape	SMD		
Elements	4		
Center Frequency	455.0kHz		
Center Frequency Tolerance	±1kHz		
Nominal Center Value	No		
6dB Bandwidth	fn±3.0kHzmin.		
Stop Bandwidth	10.0kHz		
Area of Stop Bandwidth	[within 40dB]		
Stop Band Attenuation	25dB[within fn±100kHz]		
Insertion Loss	7.0dB[at minimum loss point]		
Ripple	1.0dB[within fn±2kHz]		
GDT Deviation	25.0µs[within fn±2kHz]		
Input/Output Impedance	1500Ω		

2 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date.


Please download the latest datasheet of CFUKG455KH1X-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-US/products/productdetail?partno=CFUKG455KH1X-R0

CFUKG455KH1X-R0








Frequency Characteristics

Spurious Response



Rg+R1=R2=Input/Output Impedance

Measurement Circuit

3 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

