

Product Search Data Sheet

LFB182G45BG5D920

In Production Recommended RoHS REACH



Packaging Information

Packaging	Specifications	Minimum
		Order
		Quantity
-	180mm Paper Tape	4000



Features

Ultra-small, low-proffied, lightweight chip ffiters based on ceramic multilayer technology. Extremely ultra-small band-bass ffiters.

1. Ultra-small, low-proffied, lightweight band-pass ffiters.

- 2. Absolutely no adjustment required.
- 3. Reffow solderable.
- 4. Available in tape and reel packagings for automatic mounting.
- 5. Available in the 2400MHz to 2500MHz frequency range.

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date. Please download the latest datasheet of LFB182G45BG5D920 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-US/products/productdetail?partno=LFB182G45BG5D920



Rata Product Search Data Sheet

LFB182G45BG5D920

Note: This datasheet may be out of date. Please download the latest datasheet of LFB182G45BG5D920 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-US/products/productdetail?partno=LFB182G45BG5D920

Specifications

Applications	2.4GHz Zigbee	
Nominal Center Frequency (fo)	2450.00MHz	
Bandwidth(BW)	fo±50.00MHz	
Insertion Loss in BW I)	1.6dB max. (at 25°C)	
Insertion Loss in BW II)	1.8dB max. (-40 to +85°C)	
Attenuation(Absolute Value) I)	25dB min. at 4800.00 to 5000. 00MHz	
Attenuation(Absolute Value) II)	25dB min. at 7200.00 to 7500. 00MHz	
Balance Impedance (Differential) (Nom.)	Conjugate match to TI CC26xx	
Unbalance Impedance (Nom.)	50Ω	
Power Capacity	500mW	
Operating Temperature Range	-40°C to 85°C	
L x W (size)	1.60x0.80mm	
Thickness(max.)	0.65mm	

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

